



Model: SCH-60/SCH-60A/SCH-100/SCH-200

Crimping force: 60Ton - 200Ton

Stroke: 22mm-40mm

Rated Pressure: 700bar/10000PSI

Crimping range: $\leq \Phi 60\text{mm}$ (Copper/Al tube), $\leq \Phi 26\text{mm}$ (Steel tube)

Oil cylinder type Double acting type

Weight: 220kg - 85kg

Package: Steel box

Application: Road and bridge construction and maintenance
Oil and gas industry
Military and defence departments

Sample: Contact us for free samples

Technical Specification	SCH-60	SCH-60A	SCH-100	SCH-200
Model	SCH-60	SCH-60A	SCH-100	SCH-200
Crimping force	60T	60T	100T	200T
Stroke	38mm	38.5mm	22mm	40mm
Rated Pressure	700bar/10000P SI	700bar/10000P SI	700bar/10000P SI	700bar/10000P SI
Crimping range	≤Φ60mm (Copper/Al tube), ≤Φ26mm (Steel tube)	≤Φ60mm (Copper/Al tube), ≤Φ26mm (Steel tube)	≤Φ76mm (Copper/Al tube), ≤Φ36mm (Steel tube)	≤Φ100mm (Copper/Al tube), ≤Φ50mm (Steel tube)
Oil cylinder type	Double acting type	Double acting type	Double acting type	Double acting type
Weight	25kg	20kg	31kg	85kg
Package	Steel box	Steel box	Steel box	Steel box

Ningbo Saivs Machinery Co., Ltd

Website: www.saivstool.com www.saivs-industrial.com

Phone& Whatsapp:+8613905748980 Email: seo1@saivs.com