

SE Series, Torque Socket for Wrench

Model	Socket Diagonal (mm)	Bolt Diameter (mm)	Socket Square	Socket Weight (KG)	Torque Range (Nm)		size L1 (mm)	Size D1 (mm)
SE-0133	33	M22	0.75"	1.4	200	2000	85	75
SE-0236	36	M24	1"	1.4	200	2000	85	75
SE-0241	41	M27	1"	1.4	200	2000	85	75
SE-0246	46	M30	1"	1.4	250	2500	85	75
SE-0250	50	M33	1"	2	400	4000	88	89
SE-0255	55	M36	1"	2	400	4000	88	89
SE-0360	60	M39	1.5"	2	500	5000	88	89
SE-0365	65	M42	1.5"	6.5	800	8000	136	118
SE-0370	70	M45	1.5"	6.5	1100	11000	136	118
SE-0380	80	M45	1.5"	6.5	1100	11000	136	118
SE-0390	90	M56	1.5"	7.5	1600	16000	142	123
SE-03100	100	M60	1.5"	7.5	1600	16000	142	123
SE-0490	90	M56	2"	7.5	1600	16000	142	123
SE-04100	100	M60	2"	7.5	1600	16000	142	123

SFW-A Pneumatic Torque Wrench

No-Load Speed: 18-2.2Rpm

Customized support: OEM, ODM, OBM

Minimum Torque: 240Nm

Maximum Torque: 8000Nm

Accuracy: $\pm 5\%$

Square Drive Size: 3/4" inch-1 1/2"

Weight: 4.7 - 13.2 kg

1. Extremely excellent power to weight ratio Wider torque range, suitable for multiple stations
2. The use of multi pole gearbox has no competitive reliability Constant speed and stable output
3. Gun design, in line with human mechanics, more portable
4. Torque output in forward and reverse directions
5. Low noise, non impact output torque
6. Accuracy $\pm 5\%$ (correct air supply pressure and volume are required)

