

## 1-500 Nm Plug-In Torque Wrench, DA-1 Series



The torque wrench body is made of metal structure, sturdy and durable, with a long service life.

Accuracy: Torque error value  $\pm 4\%$ .

The plastic handle of the wrench is made of aluminum alloy knurled, which has characteristics such as oil resistance, anti slip, anti drop, and durability.

The permanent torque scale on the alloy steel pipe is easy for users to read,

with a comparison between metric and English systems.

Interchangeable head design, with torque wrench head interface sizes of 9x12 concave square head and 14x18 concave square head

Each torque wrench has a unique product identification code.

Sample: Contact us for free samples

# 1-500 Nm Plug-In Torque Wrench, DA-1 Series

DA-1 Type Plug-in torque wrench									
Model Number	Torque range		Specifications	Fine Scale/N.m		Length/mm	Width/mm	Height/mm	Weight/Kg
	N.m	Lbf.ft		N.m	Lbf.ft				
DA02601	1-5	2-9	9x12	0.05	0.067	208	28	28	0.4
DA02602	2-12	2-9	9x12	0.1	0.074	208	34	30	0.4
DA02603	4-20	3-15	9x12	0.2	0.147	208	34	30	0.45
DA02604	5-25	4-19	9x12	0.2	0.147	208	34	30	0.45
DA02605	6-30	5-23	9x12	0.2	0.147	268	34	30	0.48
DA02606	10-60	9-46	9x12	0.5	0.369	268	41	34	0.8
DA02607	10-100	7-75	9x12	0.5	0.369	388	41	34	0.81
DA02608	20-100	15-75	9x12	0.5	0.369	388	41	34	0.81
DA02609	25-125	20-94	9x12	0.5	0.369	388	41	34	0.81
DA02610	40-200	30-150	14x18	1.0	0.738	448	41	34	0.87
DA02611	20-210	15-155	14x18	1.0	0.738	448	41	34	0.87
DA02612	60-300	45-226	14x18	1.0	0.738	603	45	42	1.87
DA02613	65-335	50-250	14x18	1.0	0.738	603	45	42	1.87
DA02614	65-350	50-260	14x18	1.0	0.738	603	45	42	1.87
DA02615	80-400	60-300	14x18	2.0	1.475	653	45	42	1.89
DA02616	100-500	80-376	14x18	2.0	1.475	653	45	42	1.89

## 1-500 Nm Plug-In Torque Wrench, DP-1 Series



The torque wrench body is made of metal structure, sturdy and durable, with a long service life.

Accuracy: Torque error value  $\pm 4\%$ .

The wrench's plastic handle is made of imported materials, providing oil resistance, anti-slip, anti-drop, and durability.

The permanent torque scale on the alloy steel pipe is easy for users to read, with a comparison between metric and English systems.

Interchangeable head design, includes 9x12

and 14x18 concave square heads for torque wrench interface.

Each torque wrench has a unique product identification code.

Sample: Contact us for free samples



# 1-500 Nm Plug-In Torque Wrench, DP-1 Series

DP-1 Type Plug-in torque wrench									
Model Number	Torque range		Specification	Fine Scale/N.m		Length/mm	Width/mm	Height/mm	Weight/Kg
	N.m	Lbf.ft		N.m	Lbf.ft				
DP02501	1-5	2-9	9x12	0.05	0.067	208	28	28	0.4
DP02502	2-12	2-9	9x12	0.1	0.074	208	34	30	0.4
DP02503	4-20	3-15	9x12	0.2	0.147	208	34	30	0.45
DP02504	5-25	4-19	9x12	0.2	0.147	208	34	30	0.45
DP02505	6-30	5-23	9x12	0.2	0.147	268	34	30	0.48
DP02506	10-60	9-46	9x12	0.5	0.369	268	41	34	0.8
DP02507	10-100	7-75	9x12	0.5	0.369	388	41	34	0.81
DP02508	20-100	15-75	9x12	0.5	0.369	388	41	34	0.81
DP02509	25-125	20-94	9x12	0.5	0.369	388	41	34	0.81
DP02510	40-200	30-150	14x18	1.0	0.738	448	41	34	0.87
DP02511	20-210	15-155	14x18	1.0	0.738	448	41	34	0.87
DP02512	60-300	45-226	14x18	1.0	0.738	603	45	38	1.87
DP02513	65-335	50-250	14x18	1.0	0.738	603	45	38	1.87
DP02514	65-350	50-260	14x18	1.0	0.738	603	45	38	1.87
DP02515	80-400	60-300	14x18	2.0	1.475	653	45	38	1.89
DP02516	100-500	80-376	14x18	2.0	1.475	653	45	38	1.89

## 2-500 Nm Plug-In Torque Wrench, MTE-1 Series



Supports both clockwise and counterclockwise operations

Colorful LCD display screen

Equipped with LED sound and light alarm function

Automatically reduces brightness within a minute to extend usage time

Handle made of high-quality imported material, providing excellent grip feel

Chip overload protection with bottom layer protection function

Multiple unit options available: N.m, Lb.ft, Lb.in, kg.cm

Interchangeable head design with 9x12 and 14x18 concave square head torque wrench interface.

Sample: Contact us for free samples

## 2-500 Nm Plug-In Torque Wrench, MTE-1 Series

MTE-1 Type Plug-in torque wrench									
Model Number	Torque range		Specification	Length/mm	Width/mm	Height/mm	Weight/kg	Accuracy	
	N.m	Lbf.ft						straight	burden
MTE02801	2-10	1.5-4.5	9x12	230	47	40	0.48	±2%	±3%
MTE02802	3-30	2.3-23	9x12	230	47	40	0.48	±2%	±3%
MTE02803	6-60	4.5-45	9x12	376	45	45	1.02	±1%	±2%
MTE02804	10-100	7.5-75	9x12, 14x18	376	45	45	1.02	±1%	±2%
MTE02805	20-200	15-150	14x18	557	45	45	1.48	±1%	±2%
MTE02806	30-300	23-230	14x18	557	45	45	1.48	±1%	±2%
MTE02807	50-500	38-380	14x18	557	45	45	1.78	±1%	±2%

## 1-500 Nm Plug-In Torque Wrench, T GK-1 Series



Accuracy: Level 3 with precise results and minimal deviations

Error range: Within  $\pm 3\%$ , providing highly reliable measurements with minimal deviation

Beautiful appearance, showcasing elegance and style

High torque accuracy for efficient and precise performance

Good stability, maintaining steady operation

Equipped with a differential device for enhanced stability during use

Sample: Contact us for free samples



# 1-500 Nm Plug-In Torque Wrench, TGK-1 Series

TGK-1 type Plug-in torque wrench							
Model Number	Torque range	Specification	Length/mm	Width/mm	Height/mm	Weight/kg	Fine Scale/N.m
TGK02401	1-5	9x12	200	23	23	0.3	0.1
TGK02402	2-10	9x12	200	23	23	0.3	0.2
TGK02403	5-25	9x12	340	29.5	29.5	0.5	0.25
TGK02404	20-100	9x12	430	31.5	31.5	1	1
TGK02405	40-200	14x18	600	40	40	2	1
TGK02406	60-300	14x18	600	40	40	2	1
TGK02407	100-500	14x18	650	40	40	2.2	2



## 1-500 Nm Plug-In Torque Wrench, TG-1 Series



Accuracy: Level 4, delivering exceptional precision and accuracy in measurements  
Error range: Within  $\pm 4\%$ , guaranteeing precise and consistent results for reliable measurements every time.

Component: Meticulously crafted using high-quality alloy steel for durability and performance  
Equipped with an elastic pin design, facilitating easy replacement when needed

Sample: Contact us for free samples

# 1-500 Nm Plug-In Torque Wrench, TG-1 Series

TG-1 type Plug-in torque wrench							
Model Number	Torque range	Specification	Length/mm	Width/mm	Height/mm	Weight/kg	Fine Scal/N.m
TG02301	1-5	9x12	230	28	28	0.5	0.2
TG02302	2-10	9x12	230	28	28	0.5	0.5
TG02303	5-25	9x12	230	28	28	0.5	0.5
TG02304	8-40	9x12	230	28	28	0.5	1
TG02305	10-50	9x12	230	31	31	1	1
TG02306	20-100	9x12	405	31	31	1	7.5
TG02307	40-200	9x12	405	31	31	2	7.5
TG02308	60-300	14x18	595	36	36	2	10
TG02309	150-450	14x18	645	36	36	2	10
TG02310	100-500	14x18	645	36	36	2	10

## 1-500 Nm Plug-In Torque Wrench, ACD-1 Series



Accuracy: Level 3, providing highly accurate measurements with a maximum error range of  $\pm 3\%$ .

Error range: Within  $\pm 3\%$ , ensuring precise and reliable results.

Shell: The robust exterior is meticulously crafted using premium-grade aluminum alloy, ensuring durability and longevity.

High torque accuracy and stability: This exceptional device guarantees precise torque measurements while maintaining excellent stability throughout operation.

Sample: Contact us for free samples

# 1-500 Nm Plug-In Torque Wrench,ACD-1 Series

ACD-1 Type Plug-in torque wrench							
Model Number	Torque range	Specification	Length/mm	Width/mm	Height/mm	Weight/kg	Fine Scale/N.m
ACD02701	1-5	9x12	325	76	58	0.65	0.05
ACD02702	2-10	9x12	325	76	67	0.65	0.1
ACD02703	6-30	9x12	325	76	67	0.7	0.25
ACD02704	10-50	9x12	355	76	70	0.8	0.5
ACD02705	20-100	9x12	355	76	70	0.8	1
ACD02706	40-200	14x18	650	76	76	1.7	2
ACD02707	60-300	14x18	650	76	76	1.7	3
ACD02708	100-500	14x18	950	76	97	3.9	5